

Bag melter 18 I

GR18



Bagmelter for processing of 18kg-peelable bags

GR18

Bagmelter for
18 Kg PUR-bags

SM Klebetechnik®

SM Klebetechnik
Vertriebs GmbH

Otto-Hahn-Straße 19a
D-52525 Heinsberg / Germany

Fon +49 2452 9172-0
Fax +49 2452 9172-20

info@sm-klebetechnik.de
www.sm-klebetechnik.de



Standard features:

- Temperature-lowering device
- Bayonet filter
- Pumping device with Quick Change Function
- Filter-flushing function, for increasing the lifetime of the filter
- Tank, which can be opened quickly without any tool.
- Filter block made from high-strength aluminium
- All screw threads are rolled (for increased durability)
- E-components: Siemens, Klöckner-Möller, Lenze, Weidmüller
- Replaceable heater
- Lenze drive and channel converter
- Pneumatically-controlled, 2-level bypass
- High-quality continuous binding seal (with FEP casing)
- Compact and service-friendly design

Optional features:

- Construction equipment producible for individual use
- Electronic pressure control (without bypass)
- Medium temperature acquisition
- Flow rate measurement
- Possible pump capacities of 5 kg/h, 10 kg/h, 20 kg/h and 40 kg/h
- S7/300 with Profibus, Touch Panel or OP17

Technical data:

Heating:	Electrical
Heating capacity:	10,5 KW
Melting capacity:	1 to 30 Kg/h.*
Voltage:	3/N/PE 400 V 50 Hz
Pump type:	Gear pump
Pump capacity:	max. 2 x 5 – 80 Kg/h
Pump drive:	AC-motor
Drive capacity:	250 W -750 W
Speed regulation:	Frequency controlled
Hose connections:	1-4
Dimensions L,W,H:	1086 x 682 x 2420 mm
Dimension of cartridges:	Ø280 x 300 mm

* Depends to used hot melt

**PUR-Bag melting unit for
2 Kg peelable bags**



Delivery and services are affected in accordance with the current terms of business of the **SM Klebetechnik** Vertriebs GmbH